

535,074

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 June 2004 (17.06.2004)

PCT

(10) International Publication Number
WO 2004/051494 A1

(51) International Patent Classification⁷: **G06F 15/16, 9/45**

(21) International Application Number:
PCT/FI2003/000913

(22) International Filing Date: 1 December 2003 (01.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20022116 29 November 2002 (29.11.2002) FI

(71) Applicant (for all designated States except US): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MÄKELÄ, Jakke** [FI/FI]; Vanha Hämeentie 110 D 61, FIN-20540 Turku

(FI). **VIHMALO, Jukka-Pekka** [FI/FI]; Näreikönkatu 18 E 2, FIN-33820 Tampere (FI). **AHVENAINEN, Marko** [FI/FI]; Viserryskuja 10 B 6, FIN-36110 Ruutana (FI).


(74) Agent: **KOLSTER OY AB**; Iso Roobertinkatu 23, P.O.Box 148, FIN-00121 Helsinki (FI).

(81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT (utility model), PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: **PREDICTIVE PROBABILITY ARRANGEMENT FOR LOADING FILES OVER AN INTERFACE**



(57) Abstract: A method, system, device and software products for loading files or clips thereof from a unit comprising files or clips thereof over at least one interface to a data-processing unit. The arrangement according to the invention comprises determining joint probabilities of the files or parts ("clips") thereof, energy consumptions caused by their loading and a value for maximum energy consumption. A loading order is formed for the files or clips thereof as a function of the joint probabilities. Files or clips thereof are loaded over at least one interface in the loading order, and total energy consumption caused by the loading is determined until the value of the total energy consumption exceeds the value of the maximum energy consumption. At this point, loading of the files or clips thereof is interrupted.

WO 2004/051494 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM,

- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

PREDICTIVE PROBABILITY ARRANGEMENT FOR LOADING FILES OVER AN INTERFACE

FIELD OF THE INVENTION

5 [0001] The invention relates to a probability arrangement and particularly to a predictive probability arrangement in data transmission taking place over an interface.

BACKGROUND OF THE INVENTION

10 [0002] More and more versatile and effective user applications are required of electronic devices nowadays, whereby the electronic device must be able to process large amounts of data. A mobile phone, for instance, is no longer used merely for speaking, but also as a calendar, an Internet browser, a camera or a game device, for example. Such numerous user applications require faster data transmission capability and improved efficiency in energy consumption.

15 [0003] Interfaces between electronic devices and between components of electronic devices, particularly interfaces between memories, have an essential significance for the data transmission capability of the whole electronic device. Larger amounts of data are transmitted over the interfaces, whereby the problem in the solutions according to prior art is, in particular, the
20 limited bandwidth of the interfaces, which makes the data transmission significantly slower. On the other hand, an electronic device may have a sufficient nominal bandwidth, but problems due to software, for example, may load the interface so much that the data transmission rate of the interface is insufficient for other functions. In prior art solutions, a problem is, in addition,
25 that a large part of the transmitted data may be unnecessary, which causes undue energy consumption and waste of bandwidth. When the band is loaded with unnecessary data transmission, the data transmission rate is reduced, whereby also the transmission of necessary data slows down.

30 [0004] With the known solutions of publications JP1 1306238 and US 5 553 284, a loading factor is determined for loading a file over an interface, the factor being the minimum probability the file must have in order for it to be loaded. The problem in these solutions is, however, that the energy consumption caused by the file loading is not estimated, but the loading is carried out only on the basis of joint probabilities.

BRIEF DESCRIPTION OF THE INVENTION

[0005] An object of the invention is thus to provide a method and a system implementing the method in such way that disadvantages of the above-mentioned problems can be reduced. The object of the invention is achieved with a method, system, device and software that are characterized in what is stated in the independent claims. Preferred embodiments of the invention are described in the dependent claims.

[0006] The invention is based on loading files F_i or parts ("clips") C_i thereof over an interface IF from a unit FU comprising files F_i or clips C_i thereof to a data-processing unit DU. In this context, the unit FU that comprises files F_i or clips C_i thereof refers to, for example, a server S, memory device M or any other unit comprising data. The data-processing unit DU, in turn, refers to a mobile station T, memory device M or any other unit arranged to process data. The predictive probability system according to the invention comprises determining joint probabilities JP_i of at least two files F_i or clips C_i thereof, which probabilities express probabilities with which the files F_i or clips C_i thereof are accessed, and energy consumptions W_i caused by the loading of the files F_i or clips C_i thereof. A loading order for the files F_i or clips C_i thereof is formed as a function of the joint probabilities JP_i . In addition, a value is determined for maximum energy consumption EC_{MAX} , expressing greatest allowed energy consumption caused by the loading. Files F_i or clips C_i thereof are loaded in the loading order, and at the same time, total energy consumption ΣW_i caused by the loading of said files F_i or clips C_i thereof is determined until the value of the total energy consumption ΣW_i exceeds the value of the maximum energy consumption EC_{MAX} .

[0007] According to a preferred embodiment of the invention, the loading probabilities LP_i of the files F_i or clips C_i thereof are determined from the joint probabilities JP_i , and according to a second preferred embodiment, the loading probability functions fLP_i of the files F_i or clips C_i thereof are determined either as functions of the loading probabilities LP_i or as functions of the energy consumptions W_i caused by the loading.

[0008] According to a preferred embodiment of the invention, at least one file F_i or a clip C_i thereof is loaded over an interface from a first terminal to a second terminal.

[0009] According to a preferred embodiment of the invention, the device comprises proxy functionality, wherein the proxy functionality is

arranged to transmit at least one file F_i or a clip C_i thereof to another data-processing unit as a response to a request from the data-processing unit.

[0010] Significant advantages are achieved with the arrangement according to the invention. One advantage is that the predictive probability arrangement enables the user and/or the arrangement to determine a substantially optimal arrangement between the access and loading times and the energy consumption caused by the loading. An advantage is also that predictive probability arrangement makes it possible to essentially reduce energy losses by loading in advance files that will be needed most probably; in other words, files are not loaded only in the order in which they appear. A further advantage is that as a result of the loading of the files most probably needed, excessive use of bandwidth can be reduced, whereby the operational rates of the interface increase significantly, reaching in some cases even the level of the operational rates of a high-speed interface. One advantage is that the arrangement allows efficient use of a slow interface, which can result in significant energy savings and reduced needed bandwidth. An advantage is also that the arrangement takes user cost into account for example by using cheap local network for data transmission. A further advantage is that the proxy can be made mobile as well, which means that the devices involved can function as each other's proxies.

BRIEF DESCRIPTION OF THE FIGURES

[0011] The invention will now be described in more detail in connection with preferred embodiments, with reference to the attached drawings, of which:

Figure 1 shows a simple system comprising a PROM memory, a DRAM memory and a slow interface between them;

Figure 2 shows a simple system comprising a server, a terminal and an interface between them;

Figure 3 shows a flow chart of the functionality of a predictive probability method;

Figure 4 shows the functionality of a driver for loading a file or clips thereof;

Figure 5 shows a preferred embodiment of the invention as a probability tree;

Figure 6 shows the second preferred embodiment of the invention as a probability tree;

Figure 7 shows the third preferred embodiment of the invention as a probability tree; and

5 Figure 8 shows the fourth preferred embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0012] Interfaces, such as interfaces between electronic devices and between components of electronic devices, for example memories, have a great significance for the performance of the whole system, such as a terminal,
10 and particularly for data transmission rates and energy consumption. In electronic devices, memories are generally used for storing data. Different types of memory differ from each other mostly with regard to their operational rate, storing capacity and preservability of the stored data. Therefore, electronic devices generally comprise several different memories for different
15 objects of use.

[0013] Memories can be divided into volatile and non-volatile memories on the basis of their operation. When the power supply is interrupted, a volatile memory generally loses all data it has stored, but a non-volatile memory typically preserves the data it has stored.

20 [0014] RAM memories (Random Access Memory) are usually volatile memories in which data can be entered and read when the power source is switched on. The main memory of the central unit of an electronic device, used particularly for storing programs used by the central unit and immediate results of data processing, is generally fast RAM memory.

25 [0015] The RAM memories can be further divided into SRAM memories (Static Random Access Memory) and DRAM memories (Dynamic Random Access Memory). In a SRAM memory cell, data is typically stored in a flip-flop comprising generally four to six transistors. The structure of a SRAM memory is thus complex and takes a lot of space. A SRAM memory is used
30 particularly for executing a program code and as a cache memory because of its speed and low power consumption.

[0016] A DRAM memory cell typically comprises one capacitor, in which data is stored as electric charge, and a MOSFET transistor (Metal Oxide Semiconductor Field Effect Transistor), which functions as a switch when the
35 capacitor is charged and discharged. Owing to its simple structure, a DRAM

memory is small in size and inexpensive. In order to function, a DRAM memory requires refresh functionality, i.e. recharging of the capacitor, at given intervals. Despite the refresh functionality, the DRAM memory is fast, and it is used particularly for storing data temporarily. Several fast memory types, such as a synchronous DRAM memory (Synchronous Dynamic Random Access Memory), have been developed from the DRAM memory.

[0017] A ROM memory (Read Only Memory) is a non-volatile read-only memory, which preserves the data it has stored although the power source is switched off. Storing data in a ROM memory can be permanent or reprogrammable, depending on the manufacturing technology of the ROM memory. The ROM memories can be divided into mask ROM memories, PROM memories (Programmable Read Only Memory) and EPROM memories (Erasable and Programmable Read Only Memory). ROM memories are fast and their power consumption is usually low, but they are still rather expensive. ROM memories are used particularly for mass-storing permanent data, such as for storing programs and microcodes.

[0018] In addition to the memory components presented here, there is a large number of other memory types to which predictive probability arrangement according to the invention can be applied. These include for instance rotating memory types, such as hard disks.

[0019] The predictive probability arrangement according to the invention can preferably be used to optimize energy-consuming data transmission particularly over a slow interface.

[0020] The predictive probability arrangement according to the invention can be implemented for instance in electronic devices comprising, according to Figure 1, two memory components M_1 and M_2 , such as a PROM memory (100), which is a large non-volatile memory, and a DRAM memory (102), which is a fast execution memory, there being a slow interface IF (104) between them, over which discrete files F_i (106) or clips C_i thereof are loaded.

[0021] The predictive probability arrangement is advantageous especially when the interface IF (104) is slow compared with the size of the files F_i or clips C_i thereof. Loading large files F_i (106) or clips C_i thereof over the slow interface IF (104), for example by commanding, would be slow, which would cause a slow access time of the functionality of applications for the user. Preferably, the files F_i or clips C_i thereof to be loaded have some kind of statistical or logical interdependency. The interdependency can be, for

example, loading of new web pages on the basis of the hypertext links of one web page. The predictive probability arrangement can be used even if such interdependency does not exist.

[0022] The predictive probability arrangement according to the invention can be implemented also in the system shown in Figure 2, comprising for instance a server S (200) and an electronic device, such as a terminal T (202), and an interface IF between them, such as an air interface AIF (204). The server S (200) may comprise a large amount of data linked by means of an Internet connection, for example. Usually, there is room for only a small part of the needed files F_i (206) or clips C_i thereof in the memory of the terminal T (202). Hence, the terminal T (202) can give commands for instance to the server S (200), which can transfer files F_i (206) or clips C_i thereof to the terminal T (202) over the air interface AIF (204).

[0023] The predictive probability arrangement can also be utilized for instance in game applications. A game can be directly programmed to use the arrangement according to the invention, for instance when it is decided which structure is next given to the display. By means of the predictive probability arrangement, the very high peak rates of data transmission required by game applications can be achieved by loading some of the most probable files F_i or clips C_i thereof in advance.

[0024] Figure 3 shows a flow chart of the functionality of the predictive probability method according to a preferred embodiment of the invention. First, energy consumptions W_i are determined (300) for possible files F_i or clips C_i thereof on the basis of, for example, the number of bytes, the energy consumptions having been caused by the loading of the files.

[0025] The energy consumption W_i can be determined directly as energy, for example, in which case its unit is generally mJ (millijoule). The energy consumption W_i expresses the amount of energy that the file-processing unit DU, such as a terminal T, consumes when it loads a file F_i or a clip C_i thereof. This energy is typically proportional to the length L_i of the file F_i or a clip C_i thereof, whereby the unit of the length is generally kB (kilobyte). In the first approximation, the proportionality is direct, in other words $W_i = k \cdot L_i$, where k is a constant defined experimentally. In a real system, the function can be more complex. Such a situation is possible for example when the interface IF consumes energy when initializing data transmission, or when data is transmitted over the interface IF in packets, in other words not as a continuous

flow. The interface IF may also have other non-linear features with respect to the energy consumption. Thus, in a general case $W_i = g(L_i)$, where g is a function, for example an experimentally or theoretically defined function. This dependency is, however, application-specific and does not affect the basic principle of the invention itself. The functional form of the energy consumption W_i is not defined separately here, because it is assumed to be known or empirically determined. In order to illustrate preferred embodiments of the invention, simple design and non-dimensional variables are used in the present application, and the energy consumption is determined directly as the length $W_i = L_i$ of the file or a clip thereof.

[0026] Further, joint probabilities JP_i , i.e. probabilities with which one moves to a particular file F_i , are determined (302) for the files F_i or clips C_i thereof. Determination (302) of the joint probabilities is application-specific. If, for instance, the user has loaded a web page, it can be assumed that the user will next move on to one of the hypertext links of the web page. Thus, it is advantageous to consider loading of the hypertext link at the same time. Even if no relative probabilities could be determined, a predictive probability method can be used for determining which web pages should be loaded. On the other hand, the joint probabilities JP_i of the files F_i or clips C_i thereof can be determined by means of the probability system also on the basis of the web page visiting times achieved with the files F_i or clips C_i thereof.

[0027] The loading probabilities LP_i of the files F_i or clips C_i thereof are determined (304) as products of the joint probabilities JP_i of the particular files F_i or clips C_i thereof and the loading probabilities LP_{i-1} of files F_{i-1} or clips C_{i-1} thereof preceding the particular files F_i or clips C_i thereof.

[0028] By means of the loading probabilities LP_i , so-called loading probability functions fLP_i are determined (306) which are used for determining the loading order. Depending on the application, the loading probability function fLP_i can be, for instance, directly the loading probability LP_i of the file F_i or a clip C_i thereof, the quotient of the loading probability LP_i and the energy consumption W_i or another function of the loading probability LP_i . The loading probability function fLP_i is thus application-specific and depends on the requirements set by the user. In addition, maximum energy consumption EC_{MAX} is determined (308) for the predictive probability method, the maximum energy consumption expressing the greatest allowed total energy consumption caused by the loading of the files F_i or clips C_i thereof. The optimal manner of

determination and usage of the maximum energy consumption EC_{MAX} depends on the application. The maximum energy consumption EC_{MAX} can be determined for example on the basis of the desired standby time of the device. Great maximum energy consumption EC_{MAX} usually means, in practice, that the device consumes its battery quickly. On the other hand, low maximum energy consumption EC_{MAX} generally means that the algorithm improves the operation of the system only a little, because low maximum energy consumption EC_{MAX} enables loading of only a small amount of data, whereby the probability of the required file F_i or a clip C_i thereof being already charged in advance is lower. The optimal value of maximum energy consumption EC_{MAX} can thus be preferably determined by optimizing these two requirements.

[0029] The energy consumptions W_i , joint probabilities JP_i , loading probabilities LP_i , loading probability functions fLP_i and maximum energy consumption EC_{MAX} can be determined in any order relative to each other, with the exception, however, that the loading probability functions fLP_i are determined at a later stage than the loading probabilities LP_i , and that the loading probabilities LP_i are determined at a later stage than the joint probabilities JP_i .

[0030] Power consumptions W_i , joint probabilities JP_i and values of the maximum energy consumption EC_{MAX} can preferably be redetermined periodically, on the basis of which the values of the loading probabilities LP_i and the loading probability functions fLP_i can preferably be updated. Loading (310) of the files F_i or clips C_i thereof takes place in the order of loading probability functions from the smallest to the greatest, whereby total energy consumption ΣW_i caused by the loading of the files F_i or clips C_i thereof is determined. When it is detected in the comparison (312) that the value of the total energy consumption ΣW_i caused by the loading of the files F_i or clips C_i thereof is greater than the value of the maximum energy consumption EC_{MAX} , the loading of the files F_i or clips C_i thereof is interrupted (314).

[0031] If the loading probability functions fLP_i of two or more different files are the same, the loading order can be selected from among these files, for instance randomly. In practice, in such a case, the files F_i or clips C_i thereof can alternatively be left unloaded, particularly when the joint probabilities JP_i of the files F_i or clips C_i thereof are very low and/or the files F_i or clips C_i thereof are not followed by other files to be loaded.

[0032] Figure 4 shows a preferred embodiment of the invention for loading the files F_i or clips C_i thereof over the interface IF. When the maximum energy consumption $EC_{MAX} = 0$, only the files F_i' or clips C_i' thereof that are needed are loaded, whereby no unnecessary energy consumption is caused.

5 However, the system is slow, because the files F_i' or clips C_i thereof possibly needed are not loaded in advance. The maximum energy consumption EC_{MAX} can also be determined to be greater, which speeds up the operation of the system. If the maximum energy consumption $EC_{MAX} > 1$, a driver DR (404) preferably in functional connection to an application AP (400) and a file system

10 FS (402), i.e. a system comprising files, loads files F_i (406) or clips C_i thereof in the loading probability function order from the greatest to the smallest from the file system FS (402) to a cache memory CM (408), for instance, until the driver DR (304) detects that the value of the total energy consumption ΣW_i caused by the loading of the files F_i or clips C_i thereof exceeds the value of the maximum

15 energy consumption EC_{MAX} , whereby the driver DR (404) interrupts the loading of the files F_i (406) or clips C_i thereof. The files F_i' (410) needed are then, if required, quickly retrievable from the cache memory CM (408) to provide functionality of the application AP (400).

[0033] The invention enables thus a user or system to find a

20 substantially optimal arrangement between the access time of the application AP and the total energy consumption ΣW_i caused by the loading of the files F_i or clips C_i thereof. If the file F_i' or a clip C_i thereof needed has been loaded in advance in a cache memory CM, for example, the access time for the user is short. If the file F_i' or a clip C_i' thereof needed has not been loaded in advance,

25 its access time is significantly longer. Since, however, the loading of the files F_i or clips C_i thereof consumes energy W_i , it is not advantageous to load all possible files F_i or clips C_i thereof in advance. Using a predictive probability system can result in, for instance, a significant reduction in energy consumption while, at the same time, preserving good performance of the

30 system.

[0034] The invention will next be explained with reference to a probability tree formed with the predictive probability method according to a preferred embodiment of the invention shown in Figure 5. Energy consumptions (W_1, W_2, W_3, W_4) are determined for the first possible files (F_1, F_2, F_3, F_4), which energy consumptions have been caused by the loading of

35 these files. An algorithm according to the invention calculates loading

probabilities (LP_1, LP_2, LP_3, LP_4) for the files (F_1, F_2, F_3, F_4) as a product ($LP_1 = JP_1 \times LP_0, LP_2 = JP_2 \times LP_0, LP_3 = JP_3 \times LP_0$ and $LP_4 = JP_4 \times LP_0$) of the joint probability (JP_1, JP_2, JP_3, JP_4) of each file (F_1, F_2, F_3, F_4) and the loading probability LP_0 of the file (F_0) preceding the files (F_1, F_2, F_3, F_4). In this preferred embodiment, the loading probability function fLP_i of each file F_i is directly the loading probability LP_i of the file F_i . In addition, a value is determined for the maximum energy consumption EC_{MAX} . According to Figure 5, the maximum energy consumption $EC_{MAX} = 9$. The above-mentioned values are determined in a corresponding way for other possible files F_i .

[0035] After determining the energy consumptions W_i , joint probabilities JP_i , loading probabilities LP_i , loading probability functions fLP_i and maximum energy consumption EC_{MAX} , the files are arranged as a probability tree PT according to Figure 5. Subsequently, the files are loaded in the loading probability function order from the greatest to the smallest until the value of the total energy consumption ΣW_i caused by the loading of the files is greater than the value of the maximum energy consumption EC_{MAX} . In this embodiment, the files are loaded in the order (F_2, F_3, F_4, F_{21}). For instance file F_{32} is not loaded, because the maximum energy consumption EC_{MAX} is exceeded during the loading of file F_{21} .

[0036] Figure 6 shows a second preferred embodiment of the invention, in which, according to the preferred embodiment of Figure 5, the energy consumptions (W_1, W_2, W_3, W_4) caused by the loading of possible files (F_1, F_2, F_3, F_4) and loading probabilities (LP_1, LP_2, LP_3, LP_4) for the files (F_1, F_2, F_3, F_4) are determined as a product ($LP_1 = JP_1 \times LP_0, LP_2 = JP_2 \times LP_0, LP_3 = JP_3 \times LP_0$ and $LP_4 = JP_4 \times LP_0$) of the joint probability (JP_1, JP_2, JP_3, JP_4) of each file (F_1, F_2, F_3, F_4) and the loading probability (LP_0) of the file (F_0) preceding the files (F_1, F_2, F_3, F_4). The difference is, however, that in this preferred embodiment the loading probability function fLP_i of each file F_i is proportional not only to the loading probability LP_i but also to the energy consumption W_i caused by the loading. The loading probability function fLP_i determining the loading order can thus be, for example, a ratio of the loading probability LP_i of the file F_i and the energy consumption W_i caused by the loading, i.e. $LP_i = LP_i/W_i$. In such a case, the files having a high loading probability LP_i and/or low energy consumption are loaded first. In addition, maximum energy consumption EC_{MAX} is determined, as in the previous

embodiments. The above-mentioned values are determined in a corresponding way for other possible files F_i .

5 [0037] Files are loaded in the loading probability function order from the smallest to the greatest until the value of the total energy consumption ΣW_i caused by the loading of the files is greater than or equal to the value of the maximum energy consumption EC_{MAX} . In this embodiment, the files are loaded in the order ($F_2, F_3, F_{22}, F_{21}, F_{321}, F_{41}$). File F_{32} , for instance, is not loaded, because the value of the total energy consumption ΣW_i exceeds the value of the maximum energy consumption EC_{MAX} during the loading of file F_{41} .

10 [0038] According to a preferred embodiment of the invention, energy consumptions (W_i) and the greatest allowed value EC_{MAX} of the energy consumption caused by the loading of the files F_i or clips C_i thereof are determined for the files F_i or clips C_i thereof possibly to be loaded, but the relative probabilities of the files F_i or clips C_i thereof are not known. Thus, the
15 joint probabilities JP_i of the files F_i or clips C_i thereof are determined in such a way that the joint probability of the first files F_{iA} possibly to be loaded or clips C_{iA} thereof is as follows: $JP_{iA} = 1/N_A$, where N_A is the number of first files F_{iA} possibly to be loaded. The joint probability of the next files F_{iB} possibly to be loaded or clips C_{iB} thereof is as follows: $JP_{iB} = 1/(N_A \times N_B)$, where N_B is the
20 number of the next files F_{iB} possibly to be loaded or clips C_{iB} thereof. The joint probability of the third files F_{iC} possibly to be loaded or clips C_{iC} thereof is as follows: $JP_{iC} = 1/(N_A \times N_B \times N_C)$, where N_C is the number of third files F_{iC} or clips C_{iC} thereof possibly to be loaded. Joint probabilities JP_i are formed in a corresponding way for other files F_i or clips C_i thereof possibly to be loaded.
25 The loading probability LP_i is determined as a function of the joint probability JP_i , and the loading probability function fLP_i is determined as a function of the loading probability LP_i . Files F_i or clips C_i thereof are loaded in a random order, for example, until the value of the total energy consumption ΣW_i caused by the loading is greater than or equal to the value of the maximum energy
30 consumption EC_{MAX} , at which point the loading is interrupted. Although the loading is carried out in a random order here, a statistically better system performance on average is achieved than would be without the preloading of the files F_i or clips C_i thereof, because with a predictive probability arrangement the file F_i' needed may have been preloaded, in which case its
35 access and loading times are short.

[0039] Figure 7 shows a third preferred embodiment of the invention, in which a threshold value TH is determined for the probability method, which value the loading probability function fLP_i of the file F_i or a clip C_i thereof must at least have in order for the file F_i or a clip C_i thereof to be loaded. In the case of Figure 7, the threshold value TH is determined to be 0.15. The algorithm according to the invention determines joint probabilities (JP_1, JP_2, JP_3, JP_4) for the files (F_1, F_2, F_3, F_4), on the basis of which the loading order is determined for the files F_i or clips C_i thereof. Also loading probabilities (LP_1, LP_2, LP_3, LP_4) of the files (F_1, F_2, F_3, F_4) can be determined with the method as a product ($LP_1 = JP_1 \times LP_0, LP_2 = JP_2 \times LP_0, LP_3 = JP_3 \times LP_0$ and $LP_4 = JP_4 \times LP_0$) of the loading probability LP_0 of each file (F_1, F_2, F_3, F_4) and the file (F_0) preceding the files (F_1, F_2, F_3, F_4). In this example, the loading probability function fLP_i of each file F_i is directly the loading probability LP_i of the file F_i . The above-mentioned values are determined in a corresponding way for other possible files F_i .

[0040] After determining the threshold value TH and the joint probabilities JP_i , the files are arranged as a probability tree PT according to Figure 7. After this, the files are loaded in the loading order until the probability function JP_i of the next file F_i to be loaded or its function is lower than the threshold value TH. Thus file F_{22} , for example, is not loaded. In this embodiment, the files are loaded in the order ($F_2, F_3, F_4, F_{21}, F_{32}, F_{211}$).

[0041] The predictive probability method according to the invention can be implemented with a predictive probability system according to the invention. The system comprises means for determining the energy consumptions W_i caused by the loading of the files F_i or clips C_i thereof, joint probabilities JP_i of the files F_i or clips C_i thereof, and maximum energy consumption EC_{MAX} . The functions of the system can preferably be performed with a server S or a terminal T, or performance of the functions can be divided between different units, such as the server S and the terminal T.

[0042] According to a preferred embodiment of the invention, the functionality of the system can be implemented with a driver DR comprised by the system, a program code in the driver being arranged to form the files F_i or clips C_i thereof in the loading order and to control the loading. The functionality of the system can also be implemented in such a way, for example, that what are called intelligent functionalities, such as determination of the loading order, are arranged to be performed in the application AP, and the driver DR is

arranged to search files F_i or clips C_i thereof. The driver DR can also be what is called an intelligent unit, which performs intelligent functions in addition to searching files F_i or clips C_i thereof, or the driver DR can perform intelligent functions, being, however, in functional connection to another driver DR', which is arranged to perform the searches of files F_i or clips C_i thereof.

[0043] The above describes a predictive probability method and system for loading files F_i or clips C_i thereof over an interface IF. According to a preferred embodiment, the predictive probability functionality can be achieved with a software product which preferably comprises a program code for determining the maximum energy consumption EC_{MAX} , energy consumptions W_i caused by the loading of the files F_i or clips C_i thereof and joint probabilities JP_i . The software product further comprises a software code for forming the loading order of the files F_i or clips C_i thereof as functions of the joint probabilities JP_i , for loading files F_i or clips C_i thereof, and for interrupting the loading when the value of the total energy consumption ΣW_i is greater than or equal to the value of the maximum energy consumption EC_{MAX} .

[0044] Figure 8 shows the fourth preferred embodiment of the invention for optimising data transmission. The method allows the user or system to optimise, for example, energy and cost per bit according to energy consumption or loading speed, for example.

[0045] A local network connection (818), such as Bluetooth or WLAN connection, is established between electronic devices, such as a first, a second and a third mobile terminal T_1 (800), T_2 (802) and T_3 (804) comprising local network interface LIF_1 (806), LIF_2 (808), LIF_3 (810). One or more of the terminals T_1 , T_2 , T_3 comprising remote network interface RIF_1 (812), RIF_2 (814), RIF_3 (816) are also linked to a data unit, such as data server S (820) comprising files or clips thereof via a remote network RN (822), such as GPRS. The server S may comprise a large amount of data linked by means of an Internet connection, for example. Files F_i or clips C_i thereof needed by the terminals T_1 , T_2 , T_3 are chosen and loaded by the earlier described predictive probability method from the data server S over the interface to the terminal T_1 , T_2 , T_3 memory, for example cache memory CM_1 (824), CM_2 (826), CM_3 (828).

[0046] According to a preferred embodiment of the invention, the terminals T_1 , T_2 , T_3 comprise also mass memory MM_1 (830), MM_2 (832), MM_3 (834), in which data can be saved for a longer period. Each of the terminals T_1 , T_2 , T_3 can be considered to be a proxy server for the other terminals T_1 , T_2 , T_3

linked to it directly or via one or more other terminals T_1 , T_2 , T_3 . Files F_i or clips C_i thereof can be further loaded from terminal T_1 , T_2 , T_3 to other terminals T_1 , T_2 , T_3 cache memories CM_1 (818), CM_2 (820), CM_3 (822) for example via the Bluetooth connection. The files F_i or clips C_i thereof can then be transmitted to the terminal T_1 , T_2 , T_3 executable memory EM_1 (836), EM_2 (838), EM_3 (840) in the terminal T_1 , T_2 , T_3 when needed.

[0047] According to a preferred embodiment of the invention, the proxy functionality may be implemented in some other device than the terminal T such as in an intermediate server between the terminal and the unit FU . The loading algorithm described above only needs to be modified such that the maximum energy consumption EC_{MAX} for the file F_i or clip C_i thereof needs to be modified according to the interface in question. Usually the transmission over the local network is cheaper than over the remote network. Thus, the arrangement makes it possible to take user cost into account.

[0048] It will be obvious to a person skilled in the art that as the technology advances, the basic idea of the invention can be implemented in a plurality of ways. For example, the probability tree can be created in a manner other than the one described here. Further, the invention can also be applied to systems other than the one described here. Two memory components and an arrangement comprising an interface between them is a simplified model from which it is possible to derive other arrangements to which the invention can be applied. Thus, the invention and its embodiments are not limited to the above examples, but can vary within the scope of the claims.

CLAIMS

1. A method of loading at least one file (F_i) or a part ("clip") (C_i) thereof from a unit (FU) comprising files (F_i) or clips (C_i) thereof over an interface (IF) to a data-processing unit (DU), the method comprising
5 determining joint probabilities (JP_i) of at least two files (F_i) or clips (C_i) thereof, which joint probabilities express probabilities with which one moves to said files (F_i) or clips (C_i) thereof,

characterized by

10 determining energy consumptions (W_i) caused by the loading of said at least two files (F_i) or clips (C_i) thereof over the interface (IF);

forming a loading order for said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i);

15 determining a value for maximum energy consumption (EC_{MAX}), the value expressing the greatest allowed energy consumption caused by said loading;

loading files (F_i) or clips (C_i) thereof in said loading order and determining total energy consumption (ΣW_i) caused by the loading until the value of said total energy consumption (ΣW_i) exceeds the value of the maximum energy consumption (EC_{MAX}).

20 2. A method according to claim 1,

characterized by

determining loading probabilities (LP_i) of said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i).

3. A method according to claim 2,

25 **characterized by**

determining loading probability functions (fLP_i) of said files (F_i) or clips thereof as a function of the loading probabilities (LP_i).

4. A method according to claim 2,

characterized by

30 determining loading probability functions (fLP_i) of said files (F_i) or clips (C_i) thereof as a function of the loading probabilities (LP_i) and the energy consumptions (W_i) caused by the loading.

5. A method according to any one of the preceding claims,

characterized by

redetermining the value of said energy consumptions (W_i), maximum energy consumption (EC_{MAX}) and joint probabilities (JP_i) periodically.

6. A method according to any one of the preceding claims,
characterized by

5 redetermining the values of said maximum energy consumption (EC_{MAX}) according to the interface (IF) in question.

7. A method according to claim 5 or 6,

characterized by

10 updating the values of said loading probabilities (LP_i) and loading probability functions (fLP_i) as a response to said determination.

8. A method according to any one of the preceding claims,

characterized by

15 loading at least one file (F_i) or a clip (C_i) thereof over said interface (IF) alternatively from a server (S) to a terminal (T) or from a first memory component (100) to a second memory component (102).

9. A method according to any one of the preceding claims,

characterized by

20 loading at least one file (F_i) or a clip (C_i) thereof over said interface (IF) alternatively from a first terminal (T_1) to a second terminal (T_2) over a local network interface (LIF).

10. A method according to any one of the preceding claims,

characterized by

25 loading at least one file (F_i) or a clip (C_i) thereof from a mass memory component (830) to another memory component (836) over an internal interface.

30 11. A method of loading at least one file (F_i) or a clip (C_i) thereof from a unit (FU) comprising files (F_i) or clips (C_i) thereof over an interface (IF) to a data-processing unit (DU), the method comprising determining joint probabilities (JP_i) of at least two files (F_i) or clips (C_i) thereof, which joint probabilities express probabilities with which one moves to said files (F_i) or clips (C_i) thereof,

characterized by

35 forming a loading order for said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i);

determining a threshold value (TH), which expresses a value, which the value determined as a function of the joint probability of the file (F_i) or a clip

(C_i) thereof must at least reach in order for the file (F_i) or a clip (C_i) thereof to be loaded;

loading files (F_i) or clips (C_i) thereof in said loading order and comparing the values determined as functions of the joint probabilities of the files (F_i) or clips (C_i) thereof with the threshold value (TH) until the value
5 determined as the function of the joint probability (JP_i) of the file (F_i) or a clip (C_i) thereof is smaller than the threshold value (TH).

12. A system for loading at least one file (F_i) or a clip (C_i) thereof from a unit (FU) comprising files (F_i) or clips (C_i) thereof over an interface (IF)
10 to a data-processing unit (DU), the system comprising means for determining joint probabilities (JP_i) of at least two files (F_i) or clips (C_i) thereof, which joint probabilities express probabilities with which one moves to said files (F_i) or clips thereof (C_i),

characterized in that the system comprises
15 means for determining the energy consumption (W_i) caused by the loading of said at least two files (F_i) or clips (C_i) thereof;

means for determining the loading order of said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i);

means for determining the value of maximum energy consumption
20 (EC_{MAX}), which expresses the greatest allowed energy consumption caused by said loading; and

means for loading files (F_i) or clips (C_i) thereof and determining the total energy consumption (ΣW_i) caused by the loading of the files (F_i) or clips (C_i) thereof, the means being arranged to load files (F_i) or clips (C_i) thereof until
25 the value of the total energy consumption (ΣW_i) exceeds the value of the maximum energy consumption (EC_{MAX}).

13. A system according to claim 12,

characterized in that

at least part of said means is executed as a program code of a
30 driver (DR) comprised by the system.

14. A device for loading at least one file (F_i) or a clip (C_i) thereof from a unit (FU) comprising files (F_i) or clips (C_i) thereof over an interface (IF), the device comprising means for determining joint probabilities (JP_i) of at least two files (F_i) or clips (C_i) thereof, which joint probabilities express probabilities
35 with which one moves to said files (F_i) or clips (C_i) thereof,

characterized in that the device comprises

means for determining the energy consumptions (W_i) caused by the loading of said at least two files (F_i) or clips (C_i) thereof;

means for determining the loading order of said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i);

5 means for determining the value of maximum energy consumption (EC_{MAX}), which expresses the greatest allowed energy consumption caused by said loading; and

means for requesting files (F_i) or clips (C_i) thereof and determining the total energy consumption (ΣW_i) caused by the loading, the means being
10 arranged to load files (F_i) or clips (C_i) thereof until the value of said total energy consumption (ΣW_i) exceeds the value of the maximum energy consumption (EC_{MAX}).

15. A device for forming the loading order of at least two files (F_i) or clips (C_i) thereof for loading functionality performed over an interface (IF),

15 **characterized** in that the device comprises:

means for determining the energy consumption (W_i) caused by the loading of said at least two files (F_i) or clips (C_i) thereof, and

means for determining the loading order of said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i).

20 16. A device for controlling the loading of at least two files (F_i) or clips (C_i) thereof performed over an interface (IF),

characterized in that the device comprises:

means for determining the value of maximum energy consumption (EC_{MAX}), which expresses the greatest allowed energy consumption caused by
25 said loading, and for determining the total energy consumptions (ΣW_i) caused by the loading of said files (F_i) or clips (C_i) thereof until the value of said total energy consumption (ΣW_i) exceeds the value of the maximum energy consumption (EC_{MAX}).

17. A device according to any of claims 14 – 16,

30 **characterized** in that the device comprises:

proxy functionality, which is arranged to transmit at least one file (F_i) or a clip (C_i) thereof to another data-processing unit (DU) as a response to a request from the data-processing unit (DU).

35 18. A software product for loading at least one file (F_i) or a clip (C_i) thereof from a unit (FU) comprising files (F_i) or clips (C_i) thereof over an interface (IF) to a data-processing unit (DU), the software product comprising a

software code for determining joint probabilities (JP_i) of at least two files (F_i) or clips (C_i) thereof, with which probabilities one moves to said files (F_i) or clips (C_i) thereof,

characterized in that said software product comprises:

5 a software code for determining the energy consumptions (W_i) caused by said at least two files (F_i) or clips (C_i) thereof,

a software code for forming the loading order of said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i);

10 a software code for determining the value of the maximum energy consumption (EC_{MAX}), which expresses the greatest allowed energy consumption caused by said loading; and

a software code for loading files (F_i) or clips (C_i) thereof and determining the total energy consumption (ΣW_i) caused by the loading of said files (F_i) or clips (C_i) thereof until the value of said total energy consumption
15 (ΣW_i) exceeds the value of the maximum energy consumption (EC_{MAX}).

19. A software product for forming the loading order of at least two files (F_i) or clips (C_i) thereof for loading functionality to be performed over an interface (IF),

characterized in that said software product comprises:

20 a software code for determining the energy consumptions (W_i) of said at least two files (F_i) or clips (C_i) thereof; and

a software code for forming the loading order of said files (F_i) or clips (C_i) thereof as a function of said joint probabilities (JP_i).

20. A software product for controlling the loading of at least two files
25 (F_i) or clips (C_i) thereof to be performed over an interface (IF),

characterized in that the software product comprises:

a software code for determining the value of the maximum energy consumption (EC_{MAX}), which expresses the greatest allowed energy consumption caused by said loading; and

30 a software code for loading files (F_i) or clips (C_i) thereof and determining the total energy consumption (ΣW_i) caused by the loading of said files (F_i) or clips (C_i) thereof until the value of said total energy consumption (ΣW_i) exceeds the value of the maximum energy consumption (EC_{MAX}).

1/7




Fig. 1.




Fig. 2.

2/7




Fig. 3.

3/7




Fig. 4.

4/7




Fig. 5.

5/7




Fig. 6.

6/7




Fig. 7.

7/7




Fig. 8.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/FI 2003/000913

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: G06F 15/16, G06F 9/45

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 0072518 A1 (NOKIA NETWORKS OY), 30 November 2000 (30.11.2000), page 5, line 20 - page 7, line 26, claim 1, abstract --	1-20
P,A	US 2003126232 A1 (MOGUL, J C ET AL), 3 July 2003 (03.07.2003), [0009]-[0010], claim 1, abstract --	1-20
P,A	US 6567855 B1 (TUBBS, G S ET AL), 20 May 2003 (20.05.2003), column 1, line 65 - column 2, line 9, abstract -- -----	1-20

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "B" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

3 February 2004

Date of mailing of the international search report

17 -02- 2004

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Pär Heimdal /LR
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on family members

24/12/2003

International application No.

PCT/FI 2003/000913

WO	0072518	A1	30/11/2000	AU	4365599	A	12/12/2000
				BR	9917311	A	19/02/2002
				CA	2371503	A	30/11/2000
				DE	69905623	D,T	02/10/2003
				EP	1179247	A,B	13/02/2002
				SE	1179247	T3	
				JP	2003500925	T	07/01/2003

US	2003126232	A1	03/07/2003	NONE
----	------------	----	------------	------

US	6567855	B1	20/05/2003	NONE
----	---------	----	------------	------
